



LG K7 Screen Replacement

This guide will show walk you through how to replace the screen on the LG K7.

Written By: Christopher Chheng



INTRODUCTION

Phone screens can easily break, but that does not mean you have to fork over the cash to get a new phone or pay somebody else to replace the screen for you. By following these instructions, you can replace your device screen on your own.



TOOLS:

- [Spudger](#) (1)
 - [Hair Dryer](#) (1)
 - [Phillips #0 Screwdriver](#) (1)
-

Step 1 — Screen



- Place phone face-down and use your nail to pry the back off the back.

Step 2




- Use a plastic spudger or your nail to lift the battery out of the device and put it aside.
- The battery should come out with little effort. If it does not, do not force it.

Step 3



- Use a Phillips #0 screwdriver to remove the single 3.5mm screw holding the power button and volume rocker in place and lift it out and put it to the side.

Step 4




- Use a Phillips #0 screwdriver to unscrew the three 3.5mm screws in the bottom portion of the phone and put them to the side.
- Use a spudger to pry the plastic bit off. Be warned, it will pop out and might fling itself when you attempt to pry it out.

Step 5






- Use a spudger to pry the plastic bit off.
- Warning, it will snap out and might fling itself when you attempt to pry it out.

Step 6




- Use a Phillips #0 screwdriver to unscrew the five 3.5mm screws holding the housing into the device.
- Use a spudger to pop it out of the back of the device exposing the motherboard.

Step 7



- Use a plastic spudger to lift the motherboard out of the casing.
- You must use a plastic tool for this step or you may risk damaging the motherboard.

Step 8




- Turn the device over and locate the connector between the digitizer and the motherboard.
- Use a plastic spudger to disconnect the connector.

Step 9



- Turn the screen housing over and use a hair dryer to heat the screen.
- This melts the adhesive between the screen and the housing, allowing you to separate the two.
- Be sure to evenly heat the screen and take care not to burn yourself.

Step 10



- Once the screen is heated, use a plastic spudger to attempt to peel the glass away from the housing.
- This will take some time, so take care not to break the glass.
- Once the spudger is under the glass, drag it around the edge and separate the glass and the housing.

Step 11



- You have now successfully removed the screen and digitizer from the housing.

To reassemble your device, follow these instructions in reverse order.