

Motorola Moto G 1st Generation Battery Replacement

An easy step-by-step guide for replacing your battery with minimal efforts.

Written By: Radostin Lobodov





- iFixit Opening Tools (1)
- T5 Torx Screwdriver (1)
- Tweezers (1)

Step 1 — Rear Panel







- Mefore you start following any of the steps of this guide, completely turn the device off.
- Take the plastic back cover off by either using a plastic Pry tool or simply using your hands. Start from the bottom by the charging port
- Remove any installed SIM card and memory microSD cards.
 - Push the SIM card into the phone, and the spring eject mechanism should release the card.
 - The microSD memory card(s) may not have an eject mechanism. If so, they must be removed carefully by pushing on the raised edge/bump that is built onto the card. Use your fingernail or a plastic or rubber tool, but not one that will scratch and damage the delicate card.
 - A Patience must be taken to prevent irreversible damage and loss of data on the card.

Step 2 — Removing the Screws



 Unscrew the 3.5mm screws, total of 14, located on the back protective cover by using a T5 Torx screwdriver.

Step 3 — Battery Cover





- Use a plastic opening tool to remove the protective cover.
- ↑ Carefully work the plastic tool around all the edges of the phone.
- (i) The protective cover holds the **Volume** and the **Home** buttons which might fall off the assembly when the cover is removed.

This document was generated on 2021-03-22 06:36:53 AM (MST).

Step 4 — **Disconnecting the Battery**





Disconnect the connection between the Battery and the Mother Board by using the Pry tool.

Step 5 — Removing the Battery





- With the battery already disconnected, work around its edge with the pry tool to remove it from the assembly.
- The battery is attached with a sticker, so it may take some work to pry up. Just work at it slowly and carefully until you get it.

To reassemble your device, follow these instructions in reverse order.